

CONDUTTORI PIATTI IN RAME

COPPER BARS

INTERNATIONAL
CABLES



Piatto sagomato per connessioni elettriche, applicazioni elettromeccaniche, cabine di trasformazione, blindo sbarre, sezionamento di linea. Barre di sezione e sagomatura diverse dallo standard possono essere fornite a richiesta. Le barre vengono fornite in misure standard da 4 a 5 metri.

NORME / UNI EN 13601.

CARATTERISTICHE PRINCIPALI

Spessore nominale (s) Nominal thickness (s) [mm ²]	Minima larghezza nominale (l) Minimum nominal width (l) [mm]	Massima larghezza nominale (l) Maximum nominal width (l) [mm]
2/3	10	60
4	10	80
5/6	10	150
8	10	150
10	10	200
12	20	200
15	20	200

Il prodotto piatto rame non è incluso nel Sistema di Gestione Qualità certificato ISO 9001.



Shaped bars for electrical connections, electro-mechanical applications, transformer rooms, bus-bars. Bar sections which differ from standard size or shape can be supplied on request. Bars are supplied in standard length from 4 to 5 meters.

STANDARD / UNI EN 13601.

MAIN CHARACTERISTICS

The product copper bars is not included in Quality Management System certified ISO 9001.



SPIGOLO VIVO
SHARP EDGED



SPIGOLO RAGGIO 1mm
RADIUS 1mm EDGE



SPIGOLO ARROTONDATO
ROUNDED EDGE

CU ETP 1